





STEAM GENERATOR

CARMEN PLUS

Body material

Upper body cover: PE - Lower body cover: varnished steel

Boiler material

Stainless steel AISI 304

(with interchangeable heating element)

Boiler volume

4 L

Tanks

Water: 3 L - Det: 3 L

Maximum output

3.65 kW

Boiler output

3.6 kW

Steam production

97 g/min | 5,9 Kg/h

Power supply

I~ 230 V - 50/60 Hz

Steam T°

165° C

Detergent T°

90° C - 160° C

Vacuum output

1.2 kW

Vacuum drum capacity

5,5 L

Air flow

200 m3/h

Depression

2200 mm

Power cord

8 m

Weight

33 Kg

Packaging

60x45x75 cm

advise the user about the necessity to proceed with the boiler maintenance.









APPLICATIONS









Single-phase steam generator for usage in the professional sector, with a varnished steel body, unlimited steam autonomy thanks to the automatic refilling system (electromechanical water level control system inside the boiler – True Temp TM). Possibility to inject detergent (or hot water as optional) together with steam. Equipped with a wet&dry vacuum cleaner with float. The steam generator's front panel is equipped with an electric console with commands for a timer, a thermometer and a pressure gauge; the digital display will





TOOLS



RADAMES 6 BAR Steam & vacuum 165° C



STAR 6 BAR Steam & vacuum 165° C



JULY 6 BAR Steam 165° C



CHEWING GUM REMOVAL Steam & vacuum 165° C



Steam 165° C





